


GAS DETECTION

IP55 Pellistor detectors

The detector is equipped with a head with a Pellistor sensitive element that measures the concentration of the explosive gas on the LEL (Lower Explosive Limit) scale.

With this type of sensitive element, the correct reading is ensured, even in bad environmental conditions.

The detector is delivered with a pre-alarm threshold of 15% and an alarm threshold of 30% of the LEL.



Optionally, an interface with Android App and a PC software are available, which allow the field testing of the detector, and the modification of detection thresholds, alarm filters, addressing, full scale, etc.

The detector is equipped with an ADFT IP55 certified dust-proof metal box, housing both the communication electronics and the sensor element, positioned in the lower part, and protected by a special stainless-steel mesh.

The detector is supplied together with one of the following communication modules which must be selected at order.

STANDARD COMMUNICATION MODULES:

- Analog output module at 4-20 mA, both active and passive, and in positive or negative. Typical connection for PLC applications. Possibility to calibrate the full-scale values of the signal.
- 4 relay output module for fault, pre-alarm, alarm. Contact outputs can be set as NO or NC, typically used for connection to intrusion alarm control units or directly for wiring on electrical panels.
- Modbus output module for open protocol communication to management systems.

ESSER BY HONEYWELL COMMUNICATION MODULES:

- Absorption output module. It allows a direct connection of the sensor to the 808613.10 or 808623 transponders with 2 wires, without resistors. Alarm, pre-alarm, and fault signals will be displayed on a single input.
- Output module with O.C. opto-isolated NPN. A series of on-board resistors, selectable via dipswitch, allow the forwarding of the pre-alarm and alarm on two separate inputs, including the fault signal included.
- 3 relay output module for fault, pre-alarm, alarm. Contact outputs can be set as NO or NC.

FEATURES AND BENEFITS



Multiple communication modules for all kinds of applications



Easy replacement of sensor element in case of depletion or failure



Dust proof metal housing with IP55 standard for industrial use



Optionally configuration via Android App and PC software



Direct connection with ESSER by Honeywell loop transponder



Modbus Interface for communication to management systems

Honeywell

TECHNICAL DATA

TYPE	G700P-2	G701P-2	G702P-2	G704P-2	G705P-2	G706P-2
Supply voltage	12/24 Vdc					
Detection type (pre-heating of 150°)	Pellistor					
Service life in optimal conditions	3/4 years					
Current consumption in standby mode	max. 90 mA					
Current consumption in alarm mode	max. 110 mA					
Operating temperature	0 °C / +50 °C					
Treshold	0-100% LEL					
Resolution	0.05 up to 5%	0.05 up to % used	0.05 up to 1.6%	0.05 up to 4%	0.05 up to 1.7%	0.05 up to 1.7%
Linearity readout	±10%					
Precision readout @ 20 °C	±10%					
Gas response time T90	< 30 seconds					
Box	ADFT IP55					
Weight	370 g					
Dimensions HxWxD (mm)	175 x 100 x 60					
Coverage on installation	4/5 m @ ceiling	4/5 m @ ceiling	4 m @ 30 cm	4/5 m @ ceiling	4/5 m @ ceiling	4/5 m @ ceiling

ORDER INFORMATION

PART NUMBER	DESCRIPTION
G700P-2	Pellistor Methane Detector in IP55 Box.
G701P-2	Pellistor Special Gases Detector in IP55 Box. It can be customized to detect these gases: Methanol (Methyl Alcohol), Pentane, Heptane, Ethyl Acetate, Ethylene, Ethanol (Ethyl Alcohol), Butane, Hexane, Isobutane.
G702P-2	Pellistor Vapor Benzine Detector in IP55 Box.
G704P-2	Pellistor Hydrogen Detector in IP55 Box.
G705P-2	Pellistor LPG Detector in IP55 Box.
G706P-2	Pellistor Propane Detector in IP55 Box.

COMMUNICATION MODULES

Since the detectors will be pre-assembled with the communication module, please indicate in your order with two separate lines next to each other the detector type and the related communication module quantity needed.

PART NUMBER	DESCRIPTION
ES1-L7	ESSER by Honeywell Interface: absorption output module.
ES2-L7	ESSER by Honeywell Interface: output module with O.C. opto-isolated NPN.
ES3-L7	ESSER by Honeywell Interface: 3 relay output module for fault, pre-alarm, alarm.
G7-42	Analog output module at 4-20 mA
G7-RL4	4 relay output module
G7-MB	Modbus output module

**THE
FUTURE
IS
WHAT
WE
MAKE IT**